



SCOPE OF ACCREDITATION TO ISO/IEC 17025:2017
& ANSI/NCSL Z540-1-1994

HEMCO GAGE
455 Douglas Avenue
Holland, MI 49424
Sharla Rouwhorst Phone: 616 396 4604

CALIBRATION

Valid To: March 31, 2023

Certificate Number: 2279.01

In recognition of the successful completion of the A2LA evaluation process, accreditation is granted to this laboratory to perform the following calibrations^{1,4}:

I. Dimensional

Parameter/Equipment	Range	CMC ^{2,3} (\pm)	Comments
Straight Thread Plugs – Major Diameter	Up to 6 in	$(24 + 7L) \mu\text{in}$	P & W Supermicrometer™ Model C
	Up to 12 in	$(21 + 7.7L) \mu\text{in}$	Mikrokator, gage blocks
Simple Pitch Diameter	Up to 5 in (5 to 12) in	$(110 + 6.6L) \mu\text{in}$ $(120 + 6.3L) \mu\text{in}$	Mikrokator, 3-wire method custom supermic, 3-wire method
	Up to 6 in	$(130 + 1.7L) \mu\text{in}$	P & W Supermicrometer™ Model C
Lead	> 2 in & 10 TPI or Coarser	71 μin	Vertical lead checker
Half Angle	180°	4.3'	Optical comparator

Parameter/Equipment	Range	CMC ^{2,3} (±)	Comments
Straight Thread Rings – Pitch Diameter Minor Diameter	(0.05 to 5) in (5 to 12) in (0.04 to 0.3124) in (0.3125 to 7.874) in (4.331 to 12) in	(110 + 6.6L) μin (120 + 6.3L) μin (23 + 7.3L) μin (180 + 0.4L) μin (120 + 5L) μin	Master setting plug Gage pins Triga-bore (3-pt. probe) Federal int. comparator
Straight Plain Plugs – Outside Diameter	Up to 12 in Up to 12 in Up to 6 in	(23 + 7.3L) μin (5.4 + 8L) μin (18 + 6.2L) μin	Mikroktor, gage blocks P & W Labmaster™ UMM, Heidenhan
Straight Plain Rings – Inside Diameter	(0.04 to 1) in (1 to 12) in	(13 + 3.2L) μin (9 + 7.8L) μin	P & W Labmaster™ UMM
Tapered Thread Plugs – Major Diameter Simple Pitch Diameter Lead Half Angle Taper	Up to 12 in Up to 5 in (5 to 12) in > 2 in & 10 TPI or Coarser 180° Up to 6 in (6 to 12) in	(33 + 8.5L) μin (120 + 6L) μin (37 + 21L) μin 69 μin 4.3' (160 + 17L) μin (110 + 20L) μin	Mikroktor, gage blocks w/ taper block Mikroktor, 3-wire method, custom supermic, 3-wire method Vertical lead checker Optical comparator Mikroktor, custom supermic

Parameter/Equipment	Range	CMC ^{2, 3} (\pm)	Comments
Tapered Thread Rings – Pitch Diameter	(0.05 to 12) in	(150 + 9.8L) μ in	Master thread plug
Pitch Diameter Standoff	(0.05 to 12) in	(2400 + 160L) μ in	Master thread plug
Minor Diameter	(0.05 to 12) in	(120 + 5.7L) μ in	Master plain plug
Taper	(0.05 to 12) in	120 μ in	Sine plate, angle plate, gage balls, electronic amp w/probe
Tapered Plain Plugs – Outside Diameter	Up to 12 in	(98 + 3L) μ in	Custom Supermicrometer™
Taper	Up to 12 in	(140 + 4.3L) μ in	
Tapered Plain Rings – Inside Diameter	Up to 12 in	(120 + 2.7L) μ in	Master plain plug
Taper	Up to 12 in	97 μ in	Sine plate, electronic amp w/probe
Gage and Step Height	Up to 12 in	(96 + 4L) μ in	Gage blocks, electronic amp w/ probe

¹ This laboratory offers commercial calibration service.

² Calibration and Measurement Capability Uncertainty (CMC) is the smallest uncertainty of measurement that a laboratory can achieve within its scope of accreditation when performing more or less routine calibrations of nearly ideal measurement standards or nearly ideal measuring equipment. CMCs represent expanded uncertainties expressed at approximately the 95 % level of confidence, usually using a coverage factor of $k = 2$. The actual measurement uncertainty of a specific calibration performed by the laboratory may be greater than the CMC due to the behavior of the customer's device and to influences from the circumstances of the specific calibration.

³ In the statement CMC, L is the length of the unit under test in inches.

⁴ This scope meets A2LA's *P112 Flexible Scope Policy*.



Accredited Laboratory

A2LA has accredited

HEMCO GAGE

Holland, MI

for technical competence in the field of

Calibration

This laboratory is accredited in accordance with the recognized International Standard ISO/IEC 17025:2017 *General requirements for the competence of testing and calibration laboratories*. This laboratory also meets the requirements of ANSI/NC SL Z540-1-1994 and R205 – Specific Requirements: Calibration Laboratory Accreditation Program. This accreditation demonstrates technical competence for a defined scope and the operation of a laboratory quality management system (refer to joint ISO-ILAC-IAF Communiqué dated April 2017).



Presented this 7th day of May 2021.

A blue ink signature of the Vice President of Accreditation Services.

Vice President, Accreditation Services
For the Accreditation Council
Certificate Number 2279.01
Valid to March 31, 2023

For the calibrations to which this accreditation applies, please refer to the laboratory's Calibration Scope of Accreditation.