

Coupling Pins For Hose Couplings EN 561, ISO 7289

Model: **G2-8**

Inner Diameter: 8 mm

For torch side connection



The coupling pin Model G 2 allows in associate with the standard coupling an easily and cost-effective switch of different assignments without tools.

Highlights:

- Colored marking of coupling pins
- Coding of coupling pins

Threads:

In accordance with EN 560, ISO 3253 for common connections

Fuel Gas: 12.5, 16, 20 mm pin

Inert Gas/ Compressed Air: 12.5, 16, 20 mm pin

Oxygen: 12.5, 16, 20 mm pin

For additional connections please contact SuperFlash at (440) 716-9960, toll free at (888) 327-7306, or by email sales@oxyfuelsafety.com

Gas-Types:

EN 561-F: Acetylene (A), Town-Gas (C), Ethylene (E), Hydrogen (H), Natural Gas (Methane) (M), Propane (P), MPS Methylacetylen- Propadien- Mixture (Y)

EN 561-O: Oxygen (O),

EN 561-N: Compressed Air (D), Inert Gas (N)

Working pressure:

A 1.5 bar; F 20.0 bar; O 20 bar; N 20 bar

Maintenance:

Couplings and coupling pins are wearing parts and must be examined every 6 months for leaks in coupled and decoupled condition.

Design:

Other materials and surface finishing on request.