

Α.	Outside Diameter				
	Inside Diameter				
C.	Brush Filling Type				
	(nylon, polypropylene, tampico, horse hair, wire, other)				
	Bristle Diameter				
	Color			$_$ crimped \square	level 🗆
D.	Metal Channel Size #				
		width	Χ	height	
	#2 3,	/32 (.094)	Χ	3/32 (.094)	
				1/8 (.125)	
	#3 5,	/32 (.156)	Χ	5/32 (.156)	
	#4 3,	/16 (.187)	Χ	5/32 (.156) 3/16 (.187)	
	#5 1	1/4 (.250)	Χ	1/4 (.250)	
	#6 15	5/64 (.234)	Χ	11/32 (.343)	
	#7 5,	/16 (.312)	Χ	11/32 (.343) 5/16 (.312)	
	#8 23	3/64 (.359)	Χ	23/64 (.359)	
	#10 7	/16 (.437)	Χ	7/16 (.437)	
	(#4 and #7 are most common)				
E.	,				
	Aluminu	Aluminum \square			
	(galvanized is the most common)				
F.	Bristle Density				
		med	ium	☐ heav	vy 🗆
G.					,
H.	Quantity Per OrderAnnual Usage				
I.	Brush Application and/or Comments				

Minimum O.D. for the inside disk is 1 1/4".

If the brush is to fit a holder please indicate, to assure proper fit.

Please indicate any critical tolerances.

Minimum quantities may be required.

COMPANY INFO

Quotation Requested By:

Company				
Contact Person				
Address				
Telephone #				
Fax #				
F-mail Addrage				



440-542-9600 Fax 440-542-9696 E-mail info@precisionbrush.com www.precisionbrush.com 6700 Parkland Blvd., Solon, OH 44139 USA